

INDOOR UNIT SPECIFICATION

STANDARD

INDOOR UNIT

ARNU05GSJN4 / ARNU07GSJN4 / ARNU09GSJN4 / ARNU12GSJN4 / ARNU15GSJN4

ARNU18GSKN4 / ARNU24GSKN4 / ARNU30GSVA4 / ARNU36GSVA4



Model	Independent Unit	ARNU05GSJN4	ARNU07GSJN4	ARNU09GSJN4	ARNU12GSJN4	ARNU15GSJN4
Capacity	Cooling Nom kW	1.6	2.2	2.8	3.6	4.5
	Heating Nom kW	1.8	2.5	3.2	4.0	5.0
Power Input	Cooling / Heating Nom ¹⁾ W	10.0	11.0	12.0	15.0	23.0
	Cooling / Heating Rated ²⁾ W	30.0	30.0	30.0	30.0	30.0
Power Supply	Ø / V / Hz	1 / 220 - 240 / 50 1 / 220 / 60	1 / 220 - 240 / 50 1 / 220 / 60	1 / 220 - 240 / 50 1 / 220 / 60	1 / 220 - 240 / 50 1 / 220 / 60	1 / 220 - 240 / 50 1 / 220 / 60
Airflow Rate	Cooling H / M / L m ³ /min	6.8 / 6.5 / 5.9	7.2 / 6.8 / 5.9	7.8 / 7.2 / 5.9	8.5 / 7.8 / 6.8	10.5 / 9.5 / 6.8
	Heating H / M / L m ³ /min	6.8 / 6.5 / 5.9	7.2 / 6.8 / 5.9	7.8 / 7.2 / 5.9	8.5 / 7.8 / 6.8	10.5 / 9.5 / 6.8
Sound Pressure	H / M / L dBA	30 / 29 / 28	32 / 30 / 28	34 / 32 / 28	37 / 34 / 30	42 / 39 / 32
Sound Power	H / M / L dBA	54 / 53 / 52	54 / 53 / 52	55 / 54 / 52	55 / 54 / 53	58 / 56 / 54
Dimensions	Body W x H x D mm	837 x 302 x 189	837 x 302 x 189	837 x 302 x 189	837 x 302 x 189	837 x 302 x 189
Net Weight	kg	8.50	8.50	8.50	8.50	8.50
	Liquid mm	6.35	6.35	6.35	6.35	6.35
Piping Connection	Gas mm	12.7	12.7	12.7	12.7	12.7
	Drain ID mm	16.0	16.0	16.0	16.0	16.0

Model	Independent Unit	ARNU18GSKN4	ARNU24GSKN4	ARNU30GSVA4	ARNU36GSVA4
Capacity	Cooling Nom kW	5.6	7.1	8.5	10.4
	Heating Nom kW	6.3	7.5	9.2	10.8
Power Input	Cooling / Heating Nom ¹⁾ W	32.0	39.0	83	98
	Cooling / Heating Rated ²⁾ W	53.0	53.0	154	154
Power Supply	Ø / V / Hz	1 / 220 - 240 / 50 1 / 220 / 60	1 / 220 - 240 / 50 1 / 220 / 60	1 / 220 - 240 / 50 1 / 220 / 60	1 / 220 - 240 / 50 1 / 220 / 60
Airflow Rate	Cooling H / M / L m ³ /min	14.0 / 12.0 / 10.5	15.2 / 12.7 / 10.5	22.0 / 19.0 / 16.0	27.0 / 24.0 / 20.0
	Heating H / M / L m ³ /min	14.0 / 12.0 / 10.5	15.2 / 12.7 / 10.5	22.0 / 19.0 / 16.0	27.0 / 24.0 / 20.0
Sound Pressure	H / M / L dBA	43 / 39 / 34	46 / 41 / 34	48 / 45 / 42	50 / 47 / 43
Sound Power	H / M / L dBA	63 / 57 / 52	65 / 60 / 54	61 / 58 / 55	63 / 60 / 57
Dimensions	Body W x H x D mm	998 x 330 x 210	998 x 330 x 210	1,190 x 346 x 265	1,190 x 346 x 265
Net Weight	kg	12.50	12.50	19.0	19.0
	Liquid mm	6.35	9.52	9.52	9.52
Piping Connection	Gas mm	12.7	15.88	15.88	15.9
	Drain ID mm	16.0	16.0	16.0	16.0

* This product contains Fluorinated Greenhouse Gases. (R410A)

1) Nom.: Performance tested under EN14511

2) Rated: Max power input allowed for fan motor

Note: 1. Capacities are based on the following conditions

- Cooling: Indoor temp. 27°C (80.6°F) DB / 19°C (66.2°F) WB, Outdoor temp. 35°C (95°F) DB / 24°C (75.2°F) WB, Interconnecting piping length 7.5m, Level difference of zero

- Heating: Indoor temp. 20°C (68°F) DB / 15°C (59°F) WB, Outdoor temp. 7°C (44.6°F) DB / 6°C (42.8°F) WB, Interconnecting piping length 7.5m, Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification

3. ID.: Internal Diameter*

* This product contains Fluorinated Greenhouse Gases. (R410A)

1) Nom.: Performance tested under EN14511

2) Rated: Max power input allowed for fan motor

Note: 1. Capacities are based on the following conditions

- Cooling: Indoor temp. 27°C (80.6°F) DB / 19°C (66.2°F) WB, Outdoor temp. 35°C (95°F) DB / 24°C (75.2°F) WB, Interconnecting piping length 7.5m, Level difference of zero

- Heating: Indoor temp. 20°C (68°F) DB / 15°C (59°F) WB, Outdoor temp. 7°C (44.6°F) DB / 6°C (42.8°F) WB, Interconnecting piping length 7.5m, Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification

3. I.D.: Internal Diameter*