



INDOOR UNIT SPECIFICATION

ARTCOOL MIRROR

INDOOR UNIT

ARNU05GSJR4 / ARNU07GSJR4 / ARNU09GSJR4
ARNU12GSJR4 / ARNU15GSJR4

ARNU18GSKR4 / ARNU24GSKR4



Model	Independent Unit	ARNU05GSJR4	ARNU07GSJR4	ARNU09GSJR4	ARNU12GSJR4	ARNU15GSJR4
Capacity	Cooling	Nom kW	1.6	2.2	2.8	3.6
	Heating	Nom kW	1.8	2.5	3.2	4.0
Power Input	Cooling / Heating	Nom ¹⁾ W	11	12	13	15
	Cooling / Heating	Rated ²⁾ W	30	30	30	30
Power Supply		Ø / V / Hz	1 / 220 - 240 / 50 1 / 220 / 60	1 / 220 - 240 / 50 1 / 220 / 60	1 / 220 - 240 / 50 1 / 220 / 60	1 / 220 - 240 / 50 1 / 220 / 60
Airflow Rate	Cooling	H / M / L	m ³ /min	6.8 / 6.5 / 5.9	7.2 / 6.8 / 5.9	7.8 / 7.2 / 5.9
	Heating	H / M / L	m ³ /min	6.8 / 6.5 / 5.9	7.2 / 6.8 / 5.9	7.8 / 7.2 / 5.9
Sound Pressure		H / M / L	dBa	30 / 29 / 28	32 / 30 / 28	34 / 32 / 28
Sound Power		H / M / L	dBa	54 / 53 / 52	54 / 53 / 52	55 / 54 / 52
Dimensions	Body	W x H x D	mm	837 x 308 x 192	837 x 308 x 192	837 x 308 x 192
Net Weight			kg	9.2	9.2	9.2
Piping Connection	Liquid		mm	6.35	6.35	6.35
	Gas		mm	12.7	12.7	12.7
	Drain	ID	mm	16.0	16.0	16.0

*This product contains Fluorinated Greenhouse Gases. (R410A)

1) Nom. - Performance tested under EN14511

2) Rated - 1. Max power input allowed for fan motor

Cooling - Indoor temp. 27°C (80.6°F)DB / 19°C (66.2°F)WB, Outdoor temp. 35°C (95°F)DB / 24°C (75.2°F)WB, Interconnecting piping length 7.5m, Level difference of zero

Heating - Indoor temp. 20°C (68°F)DB / 15°C (59°F)WBn Outdoor temp. 7°C (44.6°F)DB / 6°C (42.8°F)WB, Interconnecting piping length 7.5m, Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification

3. I.D. - 'Internal Diameter'

Model	Independent Unit	ARNU18GSKR4	ARNU24GSKR4	
Capacity	Cooling	Nom kW	5.6	
	Heating	Nom kW	6.3	
Power Input	Cooling / Heating	Nom ¹⁾ W	32	
	Cooling / Heating	Rated ²⁾ W	53	
Power Supply		Ø / V / Hz	1 / 220 - 240 / 50 1 / 220 / 60	
Airflow Rate	Cooling	H / M / L	m ³ /min	14.0 / 12.0 / 10.5
	Heating	H / M / L	m ³ /min	14.0 / 12.0 / 10.5
Sound Pressure		H / M / L	dBa	43 / 39 / 34
Sound Power		H / M / L	dBa	63 / 57 / 52
Dimensions	Body	W x H x D	mm	998 x 345 x 212
Net Weight			kg	13.4
Piping Connection	Liquid		mm	6.35
	Gas		mm	12.7
	Drain	ID	mm	16.0

*This product contains Fluorinated Greenhouse Gases. (R410A)

1) Nom. - Performance tested under EN14511

2) Rated - 1. Max power input allowed for fan motor

Cooling - Indoor temp. 27°C (80.6°F)DB / 19°C (66.2°F)WB, Outdoor temp. 35°C (95°F)DB / 24°C (75.2°F)WB, Interconnecting piping length 7.5m, Level difference of zero

Heating - Indoor temp. 20°C (68°F)DB / 15°C (59°F)WBn Outdoor temp. 7°C (44.6°F)DB / 6°C (42.8°F)WB, Interconnecting piping length 7.5m, Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification

3. I.D. - 'Internal Diameter'