

Model Name	Factory model	-	ATUQ24GPLA4 Mexico	ABUQ24GM1A4 Mexico	ATUQ24GPLA4 Columbia	ABUQ24GM1A4 Columbia
Capacity		Btu/h	24	24.5	24	24
Power Supply		kW	220-240, 1, 50/60	220-240, 1, 50/60	220-240, 1, 50/60	220-240, 1, 50/60
Running Current	Cooling(Rated/Max)	A	9.6 / 19	9 / 19	10.3 / 19	9.5 / 19
Outdoor Fan	Type	-	Propeller	Propeller	Propeller	Propeller
	Air Flow Rate(Max)	m ³ /min x No.	50 x 1	50 x 1	50 x 1	50 x 1
Outdoor Fan Motor	Type	-	BLDC	BLDC	BLDC	BLDC
	Output	W x No.	85 x 1	85 x 1	85 x 1	85 x 1
Compressor	Type	-	Twin Rotary	Twin Rotary	Twin Rotary	Twin Rotary
	Model x No.	-	GKT208MAB x 1	GKT208MAB x 1	GKT208MAB x 1	GKT208MAB x 1
	Motor Type	-	BLDC	BLDC	BLDC	BLDC
	Motor Output	W x No.	1,500 x 1	1,500 x 1	1,500 x 1	1,500 x 1
Heat Exchanger	(Rows x Columns x FPI) x No.	-	(2 x 30 x 21) x 1	(2 x 30 x 21) x 1	(2 x 30 x 21) x 1	(2 x 30 x 21) x 1
Dimensions	Net(W x H x D)	mm	870 x 650 x 330	870 x 650 x 330	870 x 650 x 330	870 x 650 x 330
	Shipping(W x H x D)	mm	1,026 x 693 x 446	1,026 x 693 x 446	1,026 x 693 x 446	1,026 x 693 x 446
Weight	Net	kg	41.5	41.5	41.5	41.5
	Shipping	kg	45.3	45.3	45.3	45.3
Exterior	Color	-	Warm Gray	Warm Gray	Warm Gray	Warm Gray
Refrigerant	Type	-	R410A	R410A	R410A	R410A
	Precharged Amount	kg	1.1	1.1	1.1	1.1
	Additional Charging amount	g/m	40	40	40	40
	Chargeless-Pipe Length	m	7.5	7.5	7.5	7.5
	Control Type	-	EEV	EEV	EEV	EEV
Refrigerant Oil	Type	-	FVC68D	FVC68D	FVC68D	FVC68D
	Charged Volume	cc x No.	670 x 1	670 x 1	670 x 1	670 x 1
Piping Connection	Liquid	mm(inch)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)
	Gas	mm(inch)	Ø15.88 (5/8)	Ø15.88 (5/8)	Ø15.88 (5/8)	Ø15.88 (5/8)
Piping Length	IDU - ODU(Min /	m	7.5 / 50	7.5 / 50	7.5 / 50	7.5 / 50
Maximum Height Difference	IDU - ODU(Max)	m	30	30	30	30
Sound Pressure Level	Cooling	dB(A)	57.0	57.0	57.0	57.0
Connecting Cable	Power Supply Cable(H07RN-F)	mm ² x cores	2.5 x 3	2.5 x 3	2.5 x 3	2.5 x 3
Continuous Operation Range (Outdoor Temp.)	Cooling	°C(DB)	-5 ~ 50	-5 ~ 50	-5 ~ 50	-5 ~ 50

Note:

1. Wiring cable size must comply with the applicable local and national code.
2. Due to our policy of innovation some specifications may be changed without notification.
3. Sound level values are measured at anechoic chamber.

Therefore, these values can be increased owing to ambient conditions during operation.