

UNIDADES MONTADAS EN MURO

kBTu/h		9	12	18	24
kW		2.6	3.5	5.3	7.0
Unidades Montadas en Muro					
	ARTCOOL	●	●	●	●
		AMNW09GSJR0	AMNW12GSJR0	AMNW18GSKR0	AMNW24GSKR0

kBTu/h		9	12	18	24
kW		2.6	3.5	5.3	7.0
Unidades Montadas en Muro		●	●	●	●
		AMNW09GSJA0	AMNW12GSJA0	AMNW18GSKA0	AMNW24GSKA0
		Estándar			

• ARTCOOL

MODELO				AMNW09GSJR0	AMNW12GSJR0	AMNW18GSKR0	AMNW24GSKR0
Capacidad	Enfriamiento / Calefacción	Nom	kW	2.5 / 3.2	3.5 / 3.8	5.0 / 5.8	6.6 / 7.5
Potencia de Entrada		Nom	W	18	19	39	45
Corriente		Nom	A	0.16	0.17	0.28	0.33
Suministro de Potencia			Ø, V, Hz	1, 220 ~ 240, 50/60	1, 220 ~ 240, 50/60	1, 220 ~ 240, 50/60	1, 220 ~ 240, 50/60
Flujo de Aire		A / M / B	m³/min	9.1 / 7.6 / 5.0	9.6 / 8.1 / 5.0	15.5 / 13.1 / 10.5	16.1 / 13.1 / 10.5
Nivel de Ruido		A / M / B	dB(A)	38 / 33 / 26	39 / 35 / 26	47 / 42 / 34	47 / 42 / 34
Potencia Sonora			dB(A)	57	57	59	65
Rango de Deshumidificación			ℓ/h	1.1	1.2	1.9	2.6
Dimensiones		A x L x P	mm	837 x 308 x 192	837 x 308 x 192	998 x 345 x 212	998 x 345 x 212
Peso			kg	9.9	9.9	13.2	14.0
Conexiones de Tubería	Líquido		mm (pulg)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)
	Gas		mm (pulg)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 12.7 (1/2)	Ø 12.7 (1/2)
Control Remoto				O / Inalámbrico	O / Inalámbrico	O / Inalámbrico	O / Inalámbrico
Kit de purificación				-	-	-	-

• Estándar

MODELO				AMNW09GSJA0	AMNW12GSJA0	AMNW18GSKA0	AMNW24GSKA0
Capacidad	Enfriamiento / Calefacción	Nom	kW	2.5 / 3.2	3.5 / 3.8	5.0 / 5.8	6.6 / 7.5
Potencia de Entrada		Nom	W	18	19	39	45
Corriente		Nom	A	0.16	0.17	0.28	0.33
Suministro de Potencia			Ø, V, Hz	1, 220 ~ 240, 50/60	1, 220 ~ 240, 50/60	1, 220 ~ 240, 50/60	1, 220 ~ 240, 50/60
Flujo de Aire		A / M / B	m³/min	9.1 / 7.6 / 5.0	9.6 / 8.1 / 5.0	15.5 / 13.1 / 10.5	16.1 / 13.1 / 10.5
Nivel de Ruido		A / M / B	dB(A)	38 / 33 / 26	39 / 35 / 26	47 / 42 / 34	47 / 42 / 34
Potencia Sonora			dB(A)	57	57	59	65
Rango de Deshumidificación			ℓ/h	1.1	1.2	1.9	2.6
Dimensiones		A x L x P	mm	837 x 308 x 189	837 x 308 x 189	998 x 345 x 210	998 x 345 x 210
Peso			kg	8.7	8.7	12.0	12.8
Conexiones de Tubería	Líquido		mm (pulg)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)
	Gas		mm (pulg)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 12.7 (1/2)	Ø 12.7 (1/2)
Control Remoto				O / Inalámbrico	O / Inalámbrico	O / Inalámbrico	O / Inalámbrico
Kit de purificación				-	-	-	-